Application No.: 10/693,567

Response to Office Action dated 8/8/05

Due: 11/8/05

Listing of Claims:

- 1 1. (Original) A universal collar that attaches to a pump and, in turn, a container used in
- a dispenser having a keyplate, the universal collar comprising: a body having a first
- 3 flange and a second flange, wherein said flanges extend outward and are axially
- 4 spaced from each other for receiving the keyplate therebetween.
- 1 2. (Original) The universal collar of Claim 1, wherein said flanges are connected on a
- 2 forward side of the universal collar by a vertically extending rib.
- 1 3. (Original) The universal collar of Claim 1, wherein at least one of said flanges
- defines a notch on a rearward side thereof for receiving a projecting portion of the
- dispenser.
- 4. (Original) The universal collar of Claim 3, wherein said notch is centered within said
- 2 flange on said rearward side.
- 1 5. (Original) The universal collar of Claim 1, wherein said body includes a top edge,
- 2 said top edge defining a locating recess for receipt of a projection on the container,
- 3 said recess having a base and a pair of upstanding sides, wherein said sides are
- 4 circumferentially spaced from each other for receipt of the projection therebetween.
- 1 6. (Original) The universal collar of Claim 5, wherein one of said sides extends
- 2 perpendicular to said base and the other of said sides extends obliquely relative to

3 ' said base.

Application No.: 10/693,567

Response to Office Action dated 8/8/05

Due: 11/8/05

5

6

7

8

7. (Original) The universal collar of Claim 5, wherein said top edge extends axially upward relative to said first flange and extends in a circular fashion to circumscribe a portion of the container.

- 1 8. (Original) A universal collar comprising a hollow cylindrical collar having a first 2 flange and a second flange extending at least rearwardly therefrom, and axially 3 spaced to define a receiver clearance therebetween.
- 9. (Currently Amended) The universal collar of claim [4] 8, wherein said flanges extend radially outward from said collar, each flange defining a notch that opens rearwardly relative to said collar.
- 1 10. (Original) A universal collar used in conjunction with a container for securement of the container within a soap dispenser that has a housing that defines a container recess and has a receiver that includes a keyplate, the container comprising a hollow body having a neck portion; and

a universal collar comprising a body defining a bore, wherein said universal collar fits over said neck portion and receives said neck portion within said bore, and a pair of generally horizontal [planar] flanges extending radially outward from said universal collar and axially spaced from each other for receipt of the keyplate therebetween.

1 11. (New) A universal collar used in connection with a container having a pump to bypass
2 a keyplate in a soap dispenser and axially securing the container without a key, the
3 universal collar comprising: a cylindrical collar attachable to the pump; said cylindrical
4 collar having a first flange and a second flange extending at least rearwardly therefrom;
5 said flanges being axially spaced to receive the keyplate therebetween.